

GWL/ Power Group Technology Solutions – Stay Powered for the Future

GWL/Power Specification Document



GWL/Power Solar Panels



GWL/Sunny Poly 40 Wp

(i) 2015 GWL/Power



TECHNICAL SPECIFICATION

Product Information	
Product code	GWL/Sunny-40P
Cell Technology	Poly
Number of cells per module	36 cells
Size of each cell	156 x 44,3 mm
Electrical Data	
Maximal Power (Pmax)	40 Wp
Open Circuit Voltage (Voc)	22.2 V
Short Circuit Currents (Isc)	2,32 Amp
Maximum Power Point Voltage (Vmpp)	18,43 V
Maximum Power Point Current (Impp)	2,17 Amp
Maximum System Voltage	1000 V
Model Efficiency	13,17%
Thermal Data	
Nominal Operating Cell Temperature	45°C +/- 2°C
Temp. Coeff of Voc (TK Voc)	-(0,31+/-5) % / °C
Temp. Coeff of Isc (TK Isc)	+ 0.03% / °C
Temp. Coeff of Pmax (TK PMax)	-(0.38+/-0.05) % / °C
Mechanical Data	
Dimensions LxWxH	669 x 455 x 28 mm
Weight	3,35 kg

Certification



ELECTRICAL PARAMETERS GRAPH



<http://www.ev~power.eu>

EV-Power.eu managed by Global World Logistic Ltd
Prumyslova 11, CZ-10219 Prague 10, CZECH REPUBLIC (EU)

phone: +420 277 007 500, fax: +420 277 007 529, email: export@i4wifi.cz



**GWL
POWER**